



[Zoom in Picture](#)

■ Features

- Can control 2 x RS422/485 devices located virtually anywhere (via Ethernet or Internet)
- Extended temperature Range: -40°C - 75°C
- 2KV Isolation
- Built-in 1.5KV magnetic isolation
- Industrial-strength, highly reliable at all ports with surge protection 15kV ESD
- Capability for hot-swap, easy maintenance
- Provide pair-connection mode and host-based mode
- No host reboot required after adding new NPort Server
- Support Windows NT/2000,XP/2003/Vista, Windows 95/98/ME
- Support DHCP
- Self diagnostic and report

Nport 5232i-T

[Quick Link:](#) | [Features](#) | [Overview](#) | [Applications](#) | [Hardware](#) | [Interface](#) | [Performance](#) | [Configuration](#) | [Power and Environment](#) | [Operating Systems supported](#) | [Safety](#) | [Ordering Information](#) | [Optional Accessories](#) |

■ Overview

NPort Server 5232 is an industrial-strength network-based serial device server for connecting up to two devices like CNCs, PLCs, weighing scales, scanners and other devices directly to the 10/100Mbps Ethernet network running TCP/IP.

In addition to allowing serial devices to get networked, any host (PC Server or Workstation) without network access can also access remote serial device via adding NPort Server to the existing serial port. In other word, a pair of 1-port NPort Server can be configured over Ethernet and serve as a transparent serial channel without platform and distance limitation.

■ Applications

- SCADA system
- Building automation system
- Self-service banking system
- Other remote and distribute serial devices control
- Industrial / Factory / Laboratory automation
- Automatic warehouse control system
- Wafer fabrication system
- Retail system

■ Hardware

Processor	80186
I/O controller	16C550C or compatible
Memory	512K bytes
Connector type	Terminal block

[>Back to top](#)

■ Interface

LAN interface	Auto-detecting 10BaseT/100BaseT
Protocols	TCP/IP, UDP, Telnet, DHCP, ICMP, BootP, DNS, SMTP, NTP,SNMP
Serial interface	2 x RS422/485

No. of port	2
Signals	RS422 TxD+/-, RxD+/-, RTS+/-, CTS+/-, GND RS485 Data+/-, GND
>Back to top	
■ Performance	
Speed	110 - 230.4Kbps
Max. no. of ports	256 per Windows NT/2000/XP, 128 per Windows 95/98/ME
Protocols	TCP/IP, ICMP, UDP, DHCP, BootP, Telnet, SNMP, HTTP, SMTP, NTP
Flow Control	Xon/Xoff
>Back to top	
■ Configuration	
Parity	None, even, odd, space, mark
Data bits	5, 6, 7, 8
Stop bits	1, 1.5, 2
IRQ	Nil
I/O address	Nil
Server Configuration	via Web Browser Serial console Telnet console Windows Utility
>Back to top	
■ Power and Environment	
Operation temp.	-40°C - 75°C
Surge Protection	15kV ESD 2KV Isolation
Operating humidity	5% - 95%
Power requirements	Power input 12 to 48V AC Terminal block
Power Consumption	509mA @ 12V
Special	Built-in Buzzer Built-in Real time clock Built-in Watch dog
>Back to top	
■ Operating Systems supported	
Real Com Drivers	WIN95/98/ME/NT/2K/XP/2003/Vista
Real TTY Drivers	for Linux
Utilities	Nport Administrator for Win95/98/ME/NT/2K/XP/2003/Vista
Dimension	67 x 100.4 x 22mm
>Back to top	
■ Safety	
EMC	FCC Class A, CE Class A UL, TÜV
>Back to top	
■ Ordering Information	
Art.No	4708

Product Name

Nport 5232i-T

Packing list

NPort 5232i-T Serial Device Server
Quick Installation Guide
NPort Document and Software CD-ROM
Power Jack to Terminal Block Power Cable

[>Back to top](#)

■ **Optional Accessories**

[DK 35A](#)

DIN-Rail mounting kit

[>Back to top](#)

■ **Full size product image**



[>Back to top](#)