**Pixel Pitch** 



## **■** Features

- 10.4" LC Display
- nopen frame structure with strenthened glass
- heavy duty steel chassis with VESA 75/100mm
- max. Resolution 800 x 600 Pixels
- Contrast Ratio 400-1
- Brightness 220 cd
- Control on rear panel
- Dimensions 294.6 x 218.1 x 50mm

**Zoom in Picture** 

## VS open frame 10.4" LC Display

Quick Link: | Features | Specification | LCD | Environmental | Touchscreen optional | Power consumption | Ordering Information |


Construction	open frame structure with strengthened plass Heavy duty steel chassis with VESA 75/100mm standard screw holes Panel mount, Control on rear side
Display	<ul> <li>Flat Panel 10.4" color TFT, 800 x 600</li> <li>Brightness 220cd</li> <li>optional Touch screen</li> </ul>

		>Back to top
■ Specification		
Input signal	VGA, AV-in optional	
Control	on rear panel	
Power supply	external 48W DC 12V power adapter	
OS Support	MS DOS, Windows 98/SE, WIN NT4.0, W2K, XP, Vista	
Response Time	15ms Rising, 30ms Decay	
Viewing Angel	55° up to 55° L/R, 40° up to 40° U/D	
Signal Connector	15-pin mini DSUB	
<b>Function Control</b>	Brightness, Contrast, H/V Position, Color, Phase, Clock	
		>Back to top
■ LCD		
Consumption	3,3 V Low driving voltage and low power consumption	
Display type	10.4"	
Light luminance	220cd	
max Resolution	800 x 600	
max Colors	262k	
Response Time	15ms Rising, 30ms Decay	

0.264x0.264mm

Contrast Ratio	400/1	. Dook to ton
■ Environmental		>Back to top
_		
Operating Temp	0°C to 45°C	
Storage Temp	-20°C to 60°C	
Vibration	10-150Hz, 0.15mm	
Shock	30G peak acceleration, 11ms. duration	
		>Back to top
■ Touchscreen optional		
Туре	analog resistive	
Resolution	continuous	
Light transmission	79% or more	
Controller	RS232 interface or USB option	
		>Back to top
■ Power consumption		
Software Driver	support Win 98, NT, 2000, ME, XP	
Lifetime	100 million times	
Dimension	294.6 x 218.1 x 50mm	
Weight	ca. 4,0kg	
Certification	CE	
		>Back to top
■ Ordering Information		
Art.No	3109	
Product Name	VS OPM-10 LC Display	
Packing list	Open frame Displays includes LCD Panel, external Power Power Cord	er Adapter,
Versions:	OPM 10 without Touchscreen OPM 10T with Touchscreen	
		>Back to top
■ Full size product image		





1. Power switch

2-USB Touch-In

3. Com Touch. In 9. SEL.

4. VGA

5. DC • 12 • • in

6. VGA. Audio. In

7. Power Switch

8- Menu

10 · SEL ·

11 · Enter