



[Zoom in Picture](#)

■ Features

- AMD LX800, 500MHz without fan, inkl. 256MB DDR, VGA on board
- AMD CS5536 Chipset
- 2 x LAN / 4 x USB 2.0
- 4x RS232
- IEEE 1394>br>Compact Flash Adapter
- Mini PCI socket>br>Audio-out
- Power output 12V DC
- Dimensions 195 x 150.0 x 80mm
- HDD Space
- Keyboard/Mouse connector
- based on EBC 420

VS-Taskrunner LX 3120

Quick Link: | [Features](#) | [Overview](#) | [Chassis](#) | [Hardware](#) | [Memory](#) | [Video](#) | [Integrated Devices](#) | [Connectivity](#) | [Power supply](#) | [Environment](#) | [Software](#) | [Ordering Information](#) |

■ Overview

The really small, robust and powerful embedded system! Fan less, ultra High Performance, Low Power Consumption, Professional construction inside!
best solution for Thin Client, Internet Appliances, VoIP, Networking and Multimedia

■ Chassis

Construction	full size Aluminium
Mounting configuration	Desktop
Filter	no
Cooling system	passive heatsink, fanless
LED indicator	Power on/off in front , HDD/CF access, LAN access
Expansion slot	1 x Mini PCI
Dimensions	195 x 176150 x 80mm
Power switch	rear side

[>Back to top](#)

■ Hardware

Processor	AMD LX800, 500MHz
CPU socket	ETX 120 Module, with AMD LX CPU
BIOS	Award
Chipset	AMD Geode CS5536

[>Back to top](#)

■ Memory

Memory type	256MB DDR
Memory socket	one 184-pin DDR DIMM socket for 1GB max.

■ Video

VGA controller	embedded in Chipset
BUS Interface	4x AGP intern in chipset VGA

[>Back to top](#)

■ Integrated Devices

IDE	optional 2.5 HDD, 20GB
FDD	no
CD-ROM/DVD	no
Compact Flash	complete built in Optional 64MB,128MB,256MB,512MB, 1GB, 2GB Compact Flash Card
PCMCIA	no
DiskonChip	no
Specials	1 x Mini PCI socket
Watch dog Timer	Programmable watchdog timer, 1-63 sec.
Real Time clock	standard
Keyboard/Maus	PS/2 connector for Keyboard and Mouse

[>Back to top](#)

■ Connectivity

LAN	2 x RJ45, 10/100/Base Tx GigaLAN supports wake on LAN boot from LAN
USB	4x USB 2.0 supports boot function from USB
IEEE 1394	no
VGA	1 x 15-pin connector
Com Ports total	4 x DSUB 9 male, RS232
Com Port Modi	4 x RS232
LPT	1 x DSUB 25
Audio	Audio-out
TV-out	no
S-Video	no

[>Back to top](#)

■ Power supply

Output Power	12V DC
Input voltage	AC 100V - 240V, 47-63Hz
Power consumption	up to 48W

[>Back to top](#)

■ Environment

Operating Temp.	0°-50°C
Storage Temp.	-20°-+80°C

[>Back to top](#)

■ Software

Windows

Win98, NT, 2K, XP, Embedded XP

Linux

Kernel 2.4 / 2.6

[>Back to top](#)

■ Ordering Information

Art.No

163

Product Name

VS-Taskrunner LX 3120

Packing list

VS Taskrunner LX 3120 Embedded System
CD, English documentation
Power Adapter AC 230V and cable

[>Back to top](#)

■ Full size product image



[>Back to top](#)